



## TEX MULTIGRADE MOTOR OIL

### DESCRIPTION AND APPLICATIONS

**TEX Multigrade Motor Oil** provides high quality engine protection under all driving conditions and is specifically formulated to provide extra protection against the harmful effects of city driving, where cars undergo a higher stress due to constant stopping and going.

**TEX Multigrade Motor Oil** low friction formula helps improve gas mileage for long engine life and helps protect against rust, corrosion, startup wear, varnish build-up, and eliminates the need for extra oil additives. Protects against thermal breakdown which helps prevent stuck rings.

**TEX Multigrade Motor Oil** meets requirements of API SM service category and is available in viscosity grades: 5w20, 5w30, 10w30, 10w40 and 20w50. TEX Multigrade Motor Oil SAE 5w20, 5w30, 10w30 meet or exceed the demanding requirements of International Lubricant Standardization and Approval Committee (ILSAC) GF-4. ILSAC GF-4 comprises the latest standard for passenger car, van and light truck and sport utility vehicle motor oils.

Viscosity recommendations vary according to temperature and engine manufacturer. Always consult your owner's manual for the correct viscosity choice.

<i>Test</i>	<i>Typical Results</i>				
<b><u>Product Specifications:</u></b>	<b><u>5w20</u></b>	<b><u>5w30</u></b>	<b><u>10w30</u></b>	<b><u>10w40</u></b>	<b><u>20w50</u></b>
Specific Gravity (60°F)	0.860	0.870	0.880	0.887	0.883
Viscosity, @40°C, cSt	48.56	64.57	70.95	98.0	157.1
Viscosity, @ 100°C, cSt	8.71	10.7	10.6	14.5	17.8
Viscosity Index	159	156	137	135	125
Flash Point, °C (°F)	216 (420)	196 (385)	204 (400)	204 (400)	216 (420)
Pour Point, °C (°F)	-48 (-54)	-45 (49)	-36 (-33)	-25 (-13)	-25 (-13)
Color	4.0	4.0	4.5	4.5	4.5

### Packaging Specifications:

Bottle (Special Order)	32 fluid ounces (946 ml), HDPE plastic bottle
Cases/Pallet	84
Units/Case	12

Some grades and package styles are special order only.

### Product Claims:

**TEX Multigrade Motor Oil** protects today's smaller six-cylinder and four cylinder engines, as well as older, larger engines from severe driving conditions such as city driving. Meets API Service Classification and manufacturers' U.S. warranty requirements.

**Hazards:** "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressure, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition.



## TEX MULTIGRADE MOTOR OIL

“Empty” drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner.

Avoid prolonged contact with skin and frequently change soiled clothing. In case of contact, wash thoroughly with soap and water for 15 minutes or until the irritation subsides. The formation of mists should be avoided.

CAUTION: Continuous contact with used motor oil has caused skin cancer in laboratory animals. Keep out of reach of children.