



TEX MULTI-PURPOSE GL-5 GEAR LUBRICANT **80w90 and 85w140**

DESCRIPTION AND APPLICATIONS

TEX Multi-Purpose GL-5 Gear Lubricant is a premium quality, heavy-duty, extreme pressure, multi-purpose gear lubricant formulated with thermally stable lube oil base stock and a premium additive package to impart extreme pressure, anti-scuff, anti-wear, and anti-weld properties to the finished product.

Directions for use:

Fill up the reservoir with **TEX Multi-Purpose GL-5 Gear Lubricant**. Always follow the manufacturer recommendations.

Product Specifications:

<i>Typical</i>	<i>80W-90</i>	<i>85W-140</i>
Specific Gravity, (H ₂ O=1)	0.89	0.90
Viscosity, @ 100°C, cSt	13.9	24.8
Viscosity Index, min.	96	95
Flash Point, °F(°C)	400 (204)	410 (210)
Pour Point, °C(°F)	-26 (-15)	-18 (0)
Color	6.5	5.0

Packaging Specifications:

Bottle	32 fluid ounces (946 ml), HDPE plastic bottle
Case Size	N/A
Pallet size	N/A

Product Claims:

TEX Multi-Purpose GL-5 Gear Lubricant is recommended for topping-off or refilling truck, tractor, and off-road duty construction and mining equipment differentials, final drives and transmissions where an API GL-5 gear lubricant is required. The additives selected for this lubricant meet the demands of low speed, high torque truck and construction equipment service.

Hazards:

Do not pollute. Conserve resources, return used oil to collection centers. Avoid prolonged contact with skin. In case of contact, wash hands thoroughly with soap and water. Keep out of reach of children.