



H&W Petroleum Company
9617 Wallisville Rd.
Houston, Texas 77013

Product Data Sheet

Name	Revised
Premium Tractor Hydraulic Fluid	10/10/2006

- Multi-Functional
- Compatible with Original Fluids
- Field Tested and Performance Proven

Premier Tractor Hydraulic and Transmission Fluid is a true multi-service oil recommended for the hydraulic, wet brake, and transmission requirements of equipment manufacturers including John Deere, Allis-Chalmers, J.I. Case, Ford, International Harvester, Massey-Ferguson, Allison and White. It is recommended for ambient temperatures between 32°F and 104°F (0°C and 40°C).

<u>Test</u>	<u>Typicals</u>
Viscosity, CST @ 40°C	52.5
Viscosity, CST @ 100°C	7.1
API Gravity, 15.6°C	24.4
Flash Point, F, COC	405
Pour Point, F	-20
Color, ASTM	LO3.5

The values shown here are typical of current production. All of them may vary within modest ranges.

Hazards: “Empty” containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressure, cut weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition. “Empty” drums should be completely drained, properly bunged, and promptly returned to a drum re-conditioner.

Avoid prolonged contact with skin and frequently change soiled clothing. In case of contact, wash thoroughly with soap and water for 15 minutes or until the irritation subsides. The formation of mists should be avoided. Do not take internally. If swallowed, do not induce vomiting. Call physician of Poison Control Center immediately. Keep out of reach of children.

Note: This product should not be used in applications that require a Premium Tractor Hydraulic.