

SECTION VI HEALTH HAZARD INFORMATION

Recommended TLV of Product		N/A	
EYE CONTACT	May cause irritation.	SKIN CONTACT	Irritation or dermatitis with prolonged exposure.
INHALATION	Inhalation of oil mists or fumes can cause irritation of the nose, throat and upper respiratory tract. Repeated or prolonged exposure to oil mist may result in droplet deposition, oil granuloma formation, inflammation and increased incidence of infection.	INGESTION	May cause nausea, vomiting, and diarrhea. Small amount of this product, if aspirated into lungs, may cause mild to severe pulmonary injury, possibly death.
OTHER	None known.		

SECTION VII EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT	Flush with water for 15 minutes thoroughly while lifting eyelids. Consult physician if adverse effects persist.
SKIN CONTACT	Wash with soap and water thoroughly. Remove contaminated clothing and wash before re-use.
INHALATION	Remove individual to fresh air. If the affected person is not breathing, apply artificial respiration. Get medical attention if symptoms persist.
INGESTION	DO NOT INDUCE VOMITING. Consult physician immediately.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION	CONSUMER N/A	BULK HANDLING (Prolonged Exposure) If mist is generated (heating, spraying) and engineering control are not sufficient, wear approved organic vapor respirator suitable for oil mist.
VENTILATION	Use with adequate ventilation.	General.
EYE PROTECTION	N/A	Goggles or full-face shield.
PROTECTIVE CLOTHING	N/A	Neoprene gloves and apron.

SECTION IX PRECAUTIONS FOR SAFE HANDLING AND USE

SPILL OR LEAK PROCEDURE	Observing health hazards described above, ventilate area. Remove ignition sources. Absorb with inert absorbent such as clay, sand or diatomaceous earth, commercial sorbents, or recover using pumps. Scoop up used absorbent into drums.
WASTE DISPOSAL METHOD	Dispose in accordance with all local, state and federal regulations.
STORAGE AND HANDLING PRECAUTIONS	Do not store this material in open or unlabeled containers. Do not store near heat sparks, open flame or strong oxidizing agents. "Empty" containers retain product residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other source of ignition: they may explode.
OTHER PRECAUTIONS	Keep away from children and animals.

Supersedes _____

OSHA Revised _____
Title _____

While H&W Petroleum Co., Inc. believes this data is accurate as of revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for your information, investigation, and verification.

