



# HAVOLINE<sup>®</sup> AUTOMATIC TRANSMISSION FLUID TYPE F

## CUSTOMER BENEFITS

Havoline Automatic Transmission Fluid Type F delivers value through:

- **Protection** against the formation of lacquers and other harmful deposits
- **Exceptional stability** provided by excellent base oil and extra oxidation inhibitors
- **Quiet performance** — Especially effective in assuring proper action in Ford, Lincoln, and Mercury transmissions at all speeds.
- **Fast circulation during cold weather** and excellent lubricating body when hot.

## FEATURES

Havoline Automatic Transmission Fluid Type F is a high performance lubricating fluid for pre-1977 (and some 1977 to 1981) automatic transmissions built by Ford Motor Company and other makes requiring a high friction Type F fluid.

It is manufactured using selected highly refined base oils and additives that provide oxidation and thermal stability, friction control, cleanliness, load-carrying ability, corrosion and wear protection, and prevent the formation of foam.

Havoline Automatic Transmission Fluid Type F is red in color for identification and leakage control.

It protects against deposits, corrosion and wear, provides proper shifting action, resists oxidation and viscosity increase, and ensures long transmission life.

## APPLICATIONS

Havoline Automatic Transmission Fluid Type F is recommended for automatic transmissions in Ford, Mercury, and Lincoln passenger cars and light trucks manufactured by Ford Motor Company and certain other makes prior to 1977, and some makes from 1977 to 1981 (consult the vehicle owners manual).

This fluid is not to be used in Ford transmissions that require a fluid meeting Ford specification M2C138-CJ. Havoline<sup>®</sup> Automatic Transmission Fluid MERCON<sup>®1</sup>/DEXRON<sup>®2</sup>-III is the recommended fluid in this case.

Havoline Automatic Transmission Fluid Type F meets the requirements of former Ford specification M2C33-F.

Do not use in high pressure systems in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed.

## TYPICAL TEST DATA

<i>CPS Number</i>	221855
<i>MSDS Number</i>	8653
API Gravity	32.8
Viscosity, Kinematic cSt at 40°C cSt at 100°C	37.2 7.3
Viscosity, Saybolt SUS at 100°F SUS at 210°F	189 50.6
Viscosity, Brookfield cP at -18°C	1400
Viscosity Index	165
Flash Point, °C(°F)	214(417)
Pour Point, °C(°F)	-45(-49)
Color	Red

Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing.

1. MERCON is a registered trademark of Ford Motor Company.
2. DEXRON is a registered trademark of General Motors Corporation.