



TEXACO SPINDURA[®]

10, 22

CUSTOMER BENEFITS

Texaco Spindura oils deliver value through:

- **High oxidation stability** — Longer service life than with conventional lubricants.
- **Rust and corrosion protection** — Gives excellent protection against corrosion of both copper and steel.
- **Foam inhibition** — Contains special foam suppressant. Eliminates both foaming and aeration problems.
- **Excellent antiwear properties** — Maximizes spindle life by controlling wear.
- **Fast water separation** — Minimize rust problems by fast release of water.

FEATURES

Texaco Spindura oils are premium oils manufactured especially to meet the severe requirements of spindle lubrication.

They provide excellent antiwear protection, oxidation and corrosion inhibition, as well as foam suppression.

APPLICATIONS

Texaco Spindura oils are designed for use:

- in machine tool spindles
- textile applications

Do not use in high pressure systems in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed.

TYPICAL TEST DATA

	10	22
<i>CPS Number</i>	220824	220788
<i>MSDS Number</i>	8371	8640
AGMA Grade	—	—
API Gravity	27.7	33.7
Viscosity, Kinematic cSt at 40°C cSt at 100°C	10.3 2.5	23.1 4.4
Viscosity, Saybolt SUS at 100°F SUS at 210°F	63 35	120 41
Viscosity Index	48	98
Flash Point, °C(°F)	154(309)	177(351)
Pour Point, °C(°F)	-39(-38)	-36(-33)

Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing.